



KX-TA824

Advanced Hybrid Telephone System, 3 CO's, 8 Stations, Expandable to 8 CO's, 24 Stations

Especificaciones Técnicas	
Multi-Cell Wireless with Handoff	No
Built-In Voicemail Card	No
Built-in Voice Message Card	Yes
CO-Based Voice Mail Compatible	Yes
SD Card	No
Voice Mail Integration (APITS & DPITS)	Yes
Telephone Compatibility	KX-T7700, KX-T7300, KX-308XX, KX-T7000 series, KX-T7885, KX-TD7895 & KX-TD7896 as well as single line telephones
PC Programming	Yes, onsite and remote
Message Waiting (Proprietary Phones)	Yes
Dual Port Usage (Parallel SLT Station)	Yes
Capacity	3-8 CO Lines, 8-24 Extensions
Intercom Path	4 paths
Dialing Method	External: Tone/Pulse (10 pps, 20 pps) Internal: Tone/Pulse (10 pps, 20 pps)
Dialing Conversion	Tone to Pulse or Pulse to Tone
Switching	Space division CMOS Crosspoint Switch
Power Failure Transfer	Transfer: 2 CO lines to pre-assigned extensions
Back Up	Several hours with UPS (depending upon use)
Connections	CO lines: Modular Jack (RJ-11)
Door Intercom	4 Pin Modular Connector
Paging	Phono Jack
External Music	2-Conductor Jack
SMDR	RS-232C Interface Port (D-Sub, 9 Pin)
Programming	USB, RS232, Modem
Power Source	AC 120V, 60 Hz
Absent Message Capability	Up to 6
Account Code Entry	Yes
Automated Attendant (with DISA/OGM)	Yes

Automatic CO Hunting	Yes
B.G.M. (Back Ground Music) Jack	Yes
Call Back Busy	Yes
Call Forwarding	Yes
Call Hunting (Terminal or Circular)	Yes
Call Log	Yes
Call Parking Zones (10)	Yes
Call Park Retrieve	Yes
Call Pick Up	Yes
Call Retrieve from TAM	Yes
Call Transfer/Transfer Recall	Yes
Call Waiting Caller ID	Yes
Caller ID Call Logging (20 Station)	Yes
Caller ID to Single Line Device	Yes
Caller ID Call Log Lock	Yes
Caller ID Call Back	Yes
Caller ID Name and Number	Yes
Class of Service	Yes, 5
CO Limited Duration Timer	Yes
CO Line Status (Two Color LED)	Yes
Conference Calling	Yes
Data Dump (Print Out of System Program Data)	Yes
Data Line Security (for Fax or Modem)	Yes
Date and Time Display	Yes
D.I.L. (Direct in Line)	Yes
D.I.S.A. (Direct Inward System Access)	Fax Transfer, Ring Groups, Single Digit Access
Distinctive Ringing Tone (Door Phone Intercom & CO)	Yes
D.N.D. (Do Not Disturb)	Yes
Do Not Disturb Override	Yes
Maximum Door Phones	up to 4
Maximum Door Opener Contacts	up to 4
DSS/BLF Consoles	2
Duration Time of Call Display	Yes
Electronic Station Lock	Yes
Extension Groups	8
Exclusive Hold	Yes
Executive Override	Yes
External Paging Ports	Yes, 1
Flexible CO Keys (DSS/BLF, One Touch Dial)	Yes
Flexible DSS Keys (One Touch, Feature Access)	Yes
Flexible Key Assignments	Yes
Flexible Line Assignment	Yes
Flexible Night Service/Programmable/Manual	Yes
Flexible Ringing Assignment (Day, Night, Lunch)	Yes
Flexible Station Numbering	Yes

Hands-Free Answer Back Intercom	Yes
Handset/Headset-Display Phones	Yes
Hold	Yes
Hold Recall/Hold Reminder	Yes
Industry Standard Telephone Capability	Yes
Internal Paging (All Call Paging)	Yes
Internal Paging (Zone Paging)(8-Zones)	Yes
Last Number Redial	Yes
Limited Call Duration	Yes
Log In/Log Out	Yes
Memory Back-up	Yes
M.O.H. (Music on Hold Input)	Yes
Off-Hook Tone Signaling	Yes
Operator Call	Yes
Pre-Selection (Central Office or Intercom)	Yes
Privacy Release	Yes
Ringing Line Preference	Yes
Room Monitor	Yes
Saved Number Redial	Yes
Secret Dialing	Yes
S.M.D.R. (Station Message Detail Recording)	Yes
Station Name Display	Yes
Station Speed Dial	Yes
Station to Station Messaging	Yes
System Speed Dial Numbers	100
Timed Reminder	Yes
Toll Restriction	Yes
Toll Restriction Override	Yes
Tone/Pulse Conversation	Yes
Tone/Pulse Dialing (by CO Line)	Yes
Transfer (Screened/Unscreened)	Yes
Trunk Groups	Yes
Unattended Conference Call	Yes
Walking Class of Service	Yes
Pre-Installed Caller ID Card	1 card for 3 CO's
Single Line Device Integration	Yes, allows connection of many types of single-line telephone devices such as answering machines, cordless phones, fax machines, etc.
Dimensions (H x W x D)	11.2" x 14.5" x 4"
Weight	7.7 lbs

Contáctenos: (502)58061202 – (502)43898196
info@tecnisupport.com – www.tecnisupport.com